co:lab

Project:
Type:
Model: Como-WLR

Como-WLR

8W Rippled Glass Wall Mounted Luminaire

WATTAGE **8W** | **3-Step** | CRI (Ra) **>90** | **Bluetooth** | DALI | CE | WARRANTY **5YR**

IP **65** | **Flicker Free** | MAINS **DIM** | **Wall mount**

Glass Finishes

- Clear I Opal (OP)
- Smoke Grey (SG)
- Custom

Base Finishes

- White (WH)
- Black (BK)
- Natural Anodised (NA)
- Brushed Brass (BB)
- Brushed Copper (BC)
- Custom



Classic by design with a modern spin, the Como wall luminaire offers a warm and inviting glow on both vertical and horizontal surfaces. The heavy blown glass offers a smooth, even diffused illumination with no visible light source.

Designed to complement a vast range of interior designs, the Como wall light is available in multiple glass and mounting base finishes to suit almost and design intent.

Incorporating mains-dimming as standard with optional DALI-2 and Bluetooth dimming on request. The Como offers a 5 year warranty.

- Luminaire wattage: 8W (System)
- Luminous flux: 460Lm[2]
- Luminaire efficacy: 57.5Lm/W[1]
- Correlated colour temperature: 2700K, 3000K, 4000K
- Colour rendering index: >90[3]
- Mac-Adams Ellipse: 3-SDCM
- LED type: Epistar SMD LED
- Symmetrical distribution: 360°
- Outer trim Ø134mm x Depth 81mm
- Ingress protection rating: IP65
- Glass finishes: Clear/Opal, Smoke Grey, custom[4]
- Base finishes: Matte White, Matte Black, Natural Anodised, Brs. Brass, Brs. Copper, custom[4]
- Longevity: >50,000Hrs L80 B20
- Input voltage: 220-240VAC, 50-60Hz
- Driver: Mains-dimmable as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request[4]
- Weight: 1.65Kg
- Warranty: 5 years[5]

Model	Luminous Flux[2]	System Wattage	CCT	CRI[3]	Distribution
COMO-WLR-8W-27K	400Lm	8W	2700K	>90	360°
COMO-WLR-8W-3K	460Lm	8W	3000K	>90	360°
COMO-WLR-8W-4K	495Lm	8W	4000K	>90	360°

For Mains-dimming add suffix MD
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: COMO-WLR-8W-3K-360-MD-(OP/BB)

Model		Wattage		CCT		Distribution		Driver		Glass Finish / Base Finish
COMO-WLR	+	8W	+	3K	+	360	+	MD	+	OP/BB

1 Luminaire efficacy based on 3000K; CCT variation will alter efficacy
2 +/- 10% stated initial LED luminous flux tolerance
3 Colour Rendering Index: >90 Standard
4 Additional charges apply for non-standard colour/s and dimming options. DALI-2 and Bluetooth dimming require remote LED driver
5 Five year manufacturer's warranty covering product defects and performance deficiencies