

Sami

28W Acoustic Suspended Pendant




Baffle Finish

■ Specular (SP)

Acoustic PET Colours⁵

■ Cosmic Ash (01) ■ Blue Lagoon (02)

■ Leap Frog (03)



WATTAGE 28W
IP 20
UGR <19
Bluetooth
CE
WARRANTY 5YR

Suspended
CRI (Ra) >90
50°
Recyclable
Sound Absorbing
Fire Rated Class A

Meet Sami, an innovative acoustic suspended linear pendant renowned for its unique design. Crafted from 100% Polyester fibres, including 60% recyclable materials, Sami excels at softening and mitigating reverberation by absorbing specific frequencies within the mid to high ranges. Its distinctive cell-like louvre design not only minimizes glare but also elevates visual comfort.

Available in 3 colours, making it a versatile choice for various applications. Sami embodies safety, sustainability, and user well-being. It is free from toxins, irritants, and allergens, ensuring peace of mind.

Sami goes beyond traditional lighting solutions, offering advanced dimming options such as DALI-2 compatibility and the latest in Bluetooth technology.

Sami is backed by a comprehensive 5-year warranty, a testament to our commitment to quality and reliability.

- Luminaire wattage: 28W (System 30W)
- Luminous flux: 2400Lm²
- Luminaire efficacy: 80Lm/W¹
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90
- Mac-Adams Ellipse: 3-SDCM
- LED brand: Samsung SMD2835
- Glare control: UGR<19
- Symmetrical distribution: 50°
- Dimensions: W55 x H400 x L1112mm
- Ingress protection rating: IP20
- Cell-Louvre: ↓Direct Specular
- PET: 10mm board (3 Colours)⁵
- Mounting: Adjustable suspensions
- Longevity: >50,000Hrs L80 B10
- Driver: Tridonic non-dimmable LED driver as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request⁴
- Weight: 5.3kgs
- Warranty: 5 years⁶


Model	LED Output ²	Luminous Flux ²	LED Wattage	System Wattage	CCT	CRI ³	Distribution
SAMI-28W-3K	3750Lm	2250Lm	28W	30W	3000K	>90	50°
SAMI-28W-4K	3900Lm	2400Lm	28W	30W	4000K	>90	50°

For Non-dimming add suffix ND
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: SAMI-28W-4K-50-D-(01)


Model	Wattage	CCT	Distribution	Driver	Acoustic Felt Colour					
SAMI	+	28W	+	4K	+	50	+	D	+	01

Light Distribution



Utilisation Factors		Room Index												
Room Reflectance		0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00				
Ceiling	Walls	Floor	70	50	20	92	96	100	102	105	106	108	110	112

Cone Diagram



- 1 Luminaire efficacy based on CCT 4000K; CCT variation will alter efficacy
- 2 +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >90 Standard (Samsung SMD Series)
- 4 Additional charges apply for non-standard colour/s and dimming options
- 5 Despite every effort to provide an accurate colour image, actual colours may differ slightly due to different device screen settings and print type and media. It is advised that an actual colour swatch is requested prior to ordering
- 6 Five year manufacturer's warranty covering product defects and performance deficiencies