Project Type: Model:


Stitched-Up-PD50

12W / 15W Acoustic Rated Pendant



Luminaire Finishes

White (WH) Black (BK)



Accessories

Wire Suspension Kit (WSUS)

Part No: SUSKIT-3M-SIL Colour: Silver

Length: 3m Adjustable

Wire Suspension Kit (WSUS) Part No: SUSKIT-3M-BLK

Colour: Black Length: 3m Adjustable

Rod Suspension Kit (RSUS) Part No: ROD-SUS-KIT-1M-WHT Colour: White Length: 1m Adjustable

Rod Suspension Kit (RSUS)
Part No: ROD-SUS-KIT-1M-BLK
Colour: Black

Length: 1m Adjustable





Named after it's bold cross stitch pattern along the seam of this pendant, the Stitched-up is an acoustic pendant that can be tailored to suit a range of applications. Providing illumination of interior environments while reducing sound reverberation, it is useful in environments where noise is an issue such as hospitality, offices, residential, education and other commercial spaces.

Made from 5mm felt and a steel structure, the pendant comes in 4 sizes (450mm, 500mm, 600mm and 900mm diameters) and a range of colours, wattages and colour temperatures, allowing it to be fully customised to suit your project. The Stitched-up comes with a 5 year warranty.

- Luminaire wattage: 12W, 15W (System)
- Luminous flux: 1026-1142Lm, 1233-1383Lm²
- Luminaire efficacy: 84.82Lm/W, 85.69Lm/W¹
- Correlated colour temperature: 3000K, 4000K, 5000K (Dip-switch selectable)
- Colour rendering index: >853
- Mac-Adams Ellipse: 3-SDCM
- LED brand: OSRAM SMD LED
- Glare control: UGR<19
- Symmetrical distribution: 100°
- Dimension: Ø500 x Height 280mm
- Ingress protection rating: IP44 standard (LED Module)
- Luminaire finishes: White, Black
- Acoustic felt colours: 5mm (50 Colours)⁵
- Longevity: >50,000Hrs L80 B10
- Mounting: 3m adjustable wire suspensions
- Driver: Mains dimmable LED driver as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request⁴
- Weight: 2.9Kg (Inc. driver)
- Warranty: 5 years⁶

Model	Luminous Flux ²	LED Wattage	ССТ	CRI ³	Distribution
STITCHED-UP-PD50-X-12W-3K	1026Lm	12W	3000K	>85	100°
STITCHED-UP-PD50-X-12W-4K	1142Lm	12W	4000K	>85	100°
STITCHED-UP-PD50-X-12W-5K	1092Lm	12W	5000K	>85	100°
STITCHED-UP-PD50-X-15W-3K	1233Lm	15W	3000K	>85	100°
STITCHED-UP-PD50-X-15W-4K	1383Lm	15W	4000K	>85	100°
STITCHED-UP-PD50-X-15W-5K	1321Lm	15W	5000K	>85	100°

For Mains-Dimming add suffix MD For DALI-2 dimming add suffix D For BLUETOOTH dimming add suffix BT


Replace X with WSUS for wire suspension Replace X with RSUS for rod suspension

Example product order code configuration: STITCHED-UP-PD50-WSUS-15W-TRI-100-MD-(WH/17/203)

Model	:	Suspension	1	Wattage		CCT		Distribution		Driver		Luminaire Finish / PET Colour / Thread Colour
STICHED-UP-PD50	+	WSUS	+	15W	+	TRI	+	100	+	MD	+	WH / 17 / 203

Light Distribution


STITCHED-UP-PD50-15W-3K-100



AVERAGE BEAM ANGLE (50%): 97.3 DEG

| Colling | Wolls | Floor | Colling | Wolls | Colling | Wolls | Floor | Colling | Wolls | Wolls | Colling | Wolls | Coll

Cone Diagram



- 1 Luminaire efficacy based on CCT 3000K; CCT variations will alter efficacy
- +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >85 standard (OSRAM LED series)
- 4 Additional charges apply for non-standard colour/s and dimming options
 5 Some colours may not be available at time of ordering. Please confirm with CoLab prior to ordering
- 6 Five year manufacturer's warranty covering product defects and performance deficiencies



Project Type: Model:

Stitched-Up-PD50

12W / 15W **Acoustic Rated Pendant**

Acoustic Felt 5mm⁵







Iconic



Pebble Bay



Cream Curd



Wizard Grey



Foxdale 06



Mobster 07



Black Sea 08



Black Fox 09



Black Earth



Star Anise



Passion Plum



Oriental Night



Oriska Sky



Blueberry Popover



Formosa Blue



Magical Merlin



Flax Flower



French Riviera



Mermaid Tail 20



Samba Dance



Lvy League



Killarney



Garden Medley



Oak Moss



Clover Hilltop



Jive Talk



Electric Neon



Gone Bananas



Lemon Spread



Orange Blaze



Orange Poppy



Hot Lips 33



Renegade 34



Rum Runner 35







Palisade Orchid

Ruby Slippers



Muted Fuchsia

Blackberry Jam



Pink Persuasion

Stormy Purple



Rose Bud



Belgian Waffle



Applesauce



Chicory 46

English Saddle



Barefoot Beach

¹ Luminaire efficacy based on CCT 3000K; CCT variations will alter efficacy

^{+/- 10%} stated initial LED and luminous flux tolerance Colour Rendering Index: >85 standard (OSRAM LED series)

Additional charges apply for non-standard colour/s and dimming options

 $Some\ colours\ may\ not\ be\ available\ at\ time\ of\ ordering.\ Please\ confirm\ with\ CoLab\ prior\ to\ ordering$ 6 Five year manufacturer's warranty covering product defects and performance deficiencies




Project Type: Model:

Stitched-Up-PD50

12W / 15W **Acoustic Rated Pendant**





^{2 +/- 10%} stated initial LED and luminous flux tolerance

- 3 Colour Rendering Index: >85 standard (OSRAM LED series)
- Additional charges apply for non-standard colour/s and dimming options
- 6 Five year manufacturer's warranty covering product defects and performance deficiencies

