

Project Type: Model:

Peeper-F60


6W Fixed LED Recessed Downlight



Luminaire Finishes

White (WH) Black (BK)





Ceiling cut-out Ø60mm / 6-25mm ceiling thickness

 WATTAGE 6W
 Ø60 ○
 UGR <19</th>
 Bluetooth %
 ZZ
 Example (€
 △
 WARRANTY 5YR

 3-Step
 CRI (Rg) >90
 24° ▲
 IP 44 ♦
 MAINS DIM ○

Peeper-F60 is a Decorative, LED, ceiling recessed luminaire providing symmetrical light distribution in a quality constructed fitting. With a minimal design in either black or white and a distinct optical lens, it is a unique fitting suited to a wide range of applications.

Peeper-F60 features a Zhaga compliant LED from Bridgelux and comes in a wide range of colour temperatures and dimming options from Mains dimming through to DALI-2 and Bluetooth.

The Peeper-F series comes with a 5 year warranty.

- Luminaire wattage: 6W (System 7W)
- Luminous flux: 382-400Lm²
- Luminaire efficacy: 54.57Lm/W
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >903
- Mac-Adams Ellipse: 3-SDCM
- LED Brand: Bridgelux COB LED
- Glare control: <19
- Symmetrical distribution: 24°
- Outer trim Ø68mm; ceiling cut-out Ø60mm
- Ingress protection rating: IP44
- Luminaire finishes: White, Black
- Longevity: >50,000Hrs L80 B10
- Driver: Mains dimmable as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request⁴
- Weight: 200g (excluding driver)
- Warranty: 5 years⁵

Model	LED Output ²	Luminous Flux ²	LED Wattage	System Wattage	ССТ	CRI ³	Distribution
PEEPER-F60-6W-3K	608Lm	382Lm	6W	7W	3000K	>90	24°
PEEPER-F60-6W-4K	640Lm	400Lm	6W	7W	4000K	>90	24°


For MAINS dimming add suffix MD For DALI-2 dimming add suffix D For BLUETOOTH dimming add suffix BT

Example product order code configuration: PEEPER-F60-W-3K-24-MD-(WH)

Model		Wattage		CCT		Distribution		Driver		Luminaire Finish		
PEEPER-F60	+	6W	+	3K	+	24	+	MD	+	WH		


Light Distribution

PEEPER-F60-6W-3K-24



AVERAGE BEAM ANGLE (50%): 22.2 DEG

Cone Diagram



- 1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
- 2 +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >90 Standard, (Bridgelux COB Series)
- Charges apply for non-standard colour/s and dimming options
 Five year manufacturer's warranty covering product defects and performance deficiencies