

Project Type: Model:

Chopstix-1212-REC

Recessed Mounted Linear LED Profile



Chopstix linear profile series offers new lighting possibilities for a multitude of project applications

due to it's small size. Being recessed mounted, makes

a perfect solution for handrails, joinery intergration,

task lighting and architectural features.

Recessed _ 110° 📥 IP 44 🌢 WARRANTY 5YR

Constructed from high grade 6063T extruded aluminium with natural anodised surface treatment as standard, it provides optimal heat transfer and continuous illumination. Optional surface finishes are available to complement interior and/or exterior colour palettes. High quality opal PMMA diffusers enable harmonious distribution minimising the visibility of dots when used in conjunction with the Deltaflex-mini & Zeroflex-mini LED flex series.

- Mounting: Recessed mounting applications
- Construction: Extruded 6063T grade aluminium mounting profile
- Finish Options: Natural anodised, White, Black and custom colours optional¹
- Diffuser: Opal PMMA
- Symmetrical Distribution: 110°
- Accessories: Mounting clips & end caps included⁴
 Dimensions: W 12mm x H 12mm x L 2500mm
- Ingress protection rating: IP44
- Specifically designed for Zeroflex-mini and Deletaflex-mini LED series strip lights³
- Warranty: 5 years⁵

Luminaire Finishes

- White (WH) Black (BK) Custom
- Natural Anodised (NA)

Profile

Aluminium Profile Part No: Chopstix-1212-REC-AP Per metre

For Black / White / Natural Anodised, add suffix -BK / -WH / -NA



Accessories

Fixed Mounting Clips⁴ Part No: Chopstix-1212-REC-MC Set of 2 pcs/set



End Caps Part No: Chopstix-1212-REC-EC Set of 2 pcs/set

For Black / White / Silver, add suffix -BK / -WH / -SV





Compatible LED strip lighting²:

Deltaflex Mini³ 12W - 120 LEDs/m 2700K - 843Lm/m 3000K - 876Lm/m 4000K - 928Lm/m 10W - 120 LEDs/m 294Lm/m 15W - 280 I FDs/m 2700K - 6000K - 1318Lm/m Zeroflex Mini³ 8W - 480 LEDs/m 2700K - 700Lm/m 3000K - 763.45Lm/m 4000K - 753.74Lm/m







- 2 LED strip not included
- Refer to Deltaflex-Mini & Zeroflex-Mini datasheet for detailed technical information
- Mounting clips are included on a basis of 2 pcs/m. Additional will incur a charge 5 Five year manufacturer's warranty covering product defects and performance deficiencies