


Orb-48-TRW100

20W Single Round 48VDC Wall Washer LED Track Luminaire



Luminaire Finishes

- Black (BK)
- White/Black (WH/BK)
- Bronze/Black (BZ/BK)



WATTAGE 20W

355° 90°

3-Step

Bluetooth

WARRANTY 5YR

VOLTAGE 48VDC

CRI (Ra) >90

IP 20

Track

WALL WASHER

A 48VDC low voltage track system is synonymous with electrical safety, permitting greater flexibility and ease of use including installation. The luminaire can be installed and moved to any position without the need for turning off the power to the track. This is due to its low voltage input of 48VDC. No tools are required, the luminaires simply snap-lock into position, remaining in place until you want to remove or re-position the luminaire.

The elegant and minimalist design permits a range of micro luminaires ranging from spots, pendants and linear sources with many features. The system features simple on/off operation with additional dimming options to suit a number of protocols such as DALI or Bluetooth dimming. The system is designed to suit applications from residential through to retail and commercial. The Orb-48-TRW100 is covered by a 5 year warranty.

- Luminaire wattage: 20W (System)
- Luminous flux: 1360Lm²
- Luminaire efficacy: 68Lm/W¹
- Correlated colour temperature: 2700K, 3000K, 4000K
- Colour rendering index: >90³
- 3-Step-MacAdams Ellipse
- LED Brand: Bridgelux COB LED
- Optical distribution: Asymmetrical
- Ø102mm Trim x 37mm Width x 155mm Length
- Luminaire finishes: Black, White/Black, Bronze/Black
- Ingress protection rating: IP20
- Working voltage: 48VDC constant voltage
- Flicker free DC-DC internal driver
- Longevity: >50,000Hrs L80 B10
- Requires 48VDC remote driver and Track-System
- Dimming: DALI-2, BLE (Casambi) on request⁴
- Weight: 410g
- Warranty: 5 year⁵

Model	LED Output ²	Luminous Flux ²	System Wattage	CCT	CRI ³	Distribution
ORB-48-TRW100-20W-3K	2815Lm	1360Lm	20W	3000K	>90	Asymmetrical


For Non-dimming add suffix ND
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: ORB-48-TRW100-20W-3K-ASY-ND-(BK)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish
ORB-48-TRW100	20W	3K	ASY	ND	BK


Light Distribution

ORB-48-TRW100-20W-3K-ASY



Room Reflectance		Utilisation Factors									
Ceiling	Walls	Room Index									
70	50	20	0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
			66	74	80	85	91	95	98	102	105

Cone Diagram




1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
2 +/- 10% stated initial LED and luminous flux tolerance
3 Colour Rendering Index: >90 Standard (Bridgelux COB Series)
4 Additional charges apply for non-standard colour/s and dimming options
5 Five year manufacturer's warranty covering product defects and performance deficiencies

Orb-48-TRW100


20W Single Round 48VDC Wall Washer LED Track Luminaire

48VDC TRACK-SYSTEM track options


Surface / Suspended Track
Product No: TR-SM26
Colour: Black
Size: W26mm x H54mm



Recessed Track
Product No: TR-REC26
Colour: Black
Size: W37mm x H54mm



Recessed Trimless Track
Product No: TR-TL26
Colour: Black
Size: W70mm x H54mm



- 1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
- 2 +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >90 Standard (Bridgelux COB Series)
- 4 Additional charges apply for non-standard colour/s and dimming options
- 5 Five year manufacturer's warranty covering product defects and performance deficiencies