


## Aero-TR72

### 22W Beam Adjustable LED Track Luminaire



Luminaire Finishes

Black (BK) White/Black (WH/BK)



**WATTAGE 22W** | **VOLTAGE 240VAC** | **Bluetooth** | **IP20** | **355°** | **90°** | **CRI (Ra) >90** | **3-Step** | **20° ~ 60° Adjustable** | **Track** | **WARRANTY 5YR**

Introducing the Aero series, an LED track-mounted architectural luminaire collection that delivers adjustable symmetrical, versatile, and low-glare lighting distribution. Its sleek, minimal design combines high-quality components within a compact housing.

Aero is exceptionally versatile, making it suitable for residential, retail spaces, offices, and commercial fit-outs. Offering a range of dimming options, from DALI-2 compatibility to the latest in Bluetooth wireless technology. Its die-cast aluminium construction ensures optimal thermal dissipation, while precision-formed optics with user-adjustable distributions offer tailored lighting.

Aero incorporates Zhaga-compliant Bridgelux LED technology paired with industry-leading driver technology, guaranteeing performance and longevity. To underscore our commitment to quality, Aero comes with a reassuring 5-year warranty.

- Luminaire wattage: 22W (System 24W)
- Luminous flux: 1660-1720Lm<sup>2</sup>
- Luminaire efficacy: 69Lm/W<sup>1</sup>
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90<sup>3</sup>
- 3-Step-MacAdams Ellipse
- LED Brand: Bridgelux COB LED
- Optical distribution: 20°~60° adjustable
- Ø72mm Trim x 167mm Length
- Luminaire finishes: Black, White/Black
- Ingress protection rating: IP20
- Longevity: >50,000Hrs L80 B10
- Requires 3-Circuit track system<sup>4</sup>
- 3-Circuit Track adaptor as standard
- Dimming: DALI-2, BLE (Casambi) on request<sup>5</sup>
- Weight: 620g
- Warranty: 5 year<sup>5</sup>

Model	LED Output <sup>2</sup>	Luminous Flux <sup>2</sup>	LED Wattage	System Wattage	CCT	CRI <sup>3</sup>	Distribution
AERO-TR72-22W-3K	2025Lm	1660Lm	22W	24W	3000K	>90	20° ~ 60°
AERO-TR72-22W-4K	2170Lm	1720Lm	22W	24W	4000K	>90	20° ~ 60°


For Non-dimming add suffix ND  
For DALI-2 dimming add suffix D  
For BLUETOOTH dimming add suffix BT

Example product order code configuration: AERO-TR72-22W-3K-20~60-ND-(WH/BK)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish
AERO-TR72	22W	3K	20~60	ND	WH/BK


#### Light Distribution

AERO-TR72-22W-3K-20-60



Utilisation Factors	
Room Reflectance	Room Index
Ceiling   Walls   Floor	0.80   1.00   1.25   1.50   2.00   2.50   3.00   4.00   5.00
70   50   20	87   92   96   99   101   103   106   108   110

#### Cone Diagram




1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy  
2 +/- 10% stated initial LED and luminous flux tolerance  
3 Colour Rendering Index: >90 Standard (Bridgelux COB Series)  
4 Charges apply for non-standard colour/s, 3-circuit track and dimming options  
5 Five year manufacturer's warranty covering product defects and performance deficiencies

## Aero-TR72


### 22W Beam Adjustable LED Track Luminaire

#### 240VAC TRACK-SYSTEM track options


3-Circuit Surface Track  
Product No: PRO-TRK-SM-3C  
Colour: White, Black, Silver  
Size: W35.2 x H32.5mm




3-Circuit Surface DALI Track  
Product No: PRO-TRK-SM-3C-D  
Colour: White, Black, Silver  
Size: W35.2 x H32.5mm



3-Circuit Recessed Track  
Product No: PRO-TRK-REC-3C  
Colour: White, Black, Silver  
Size: W56 x 35.5mm



3-Circuit Recessed DALI Track  
Product No: PRO-TRK-REC-3C-D  
Colour: White, Black, Silver  
Size: W56 x 35.5mm



- 1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
- 2 +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >90 Standard (Bridgelux COB Series)
- 4 Charges apply for non-standard colour/s, 3-circuit track and dimming options
- 5 Five year manufacturer's warranty covering product defects and performance deficiencies