




## Zen-60

### 38W-314W Suspended Circular Direct Illumination Luminaire



Luminaire Finishes



#### Options

##### Wire Suspension Kit (WSUS)

Part No: SUSKIT-3M-SIL  
Colour: Silver  
Length: 3m Adjustable



##### Wire Suspension Kit (WSUS)

Part No: SUSKIT-3M-BLK  
Colour: Black  
Length: 3m Adjustable



#### Zero Light Leak Joiner

For sizes between Ø1500mm through to Ø5000mm you have the option to utilise our proprietary joiner which totally eliminates any possible light leak. Using the joiner ensures correct alignment between the segments making installation smoother and faster.



WATTAGE 38W-314W
CRI (Ra) >90
Bluetooth
3-Step
110°
IP 40
Suspended
WARRANTY 5YR

Zen luminaires are a series of circular, oval and angular shaped luminaires that are able to be suspended, surface mounted or trimless recessed. Available in a range of sizes, they provide creative lighting possibilities for a range of applications and spaces including high end residential projects through to hotel lobbies and commercial spaces.

Custom made, it can be manufactured from diameters as small as 400mm through to sizes as large as 5000mm with custom aluminium extrusions and high end surface finishings available to suit a variety of interior spaces.

The Zen uses quality components from leading brands such as Osram Opto Semiconductors for the LED and Tridonic for the LED driver. The Zen series is covered by a 5 year warranty.

- Luminaire wattage: 38W-314W (System)
- Luminous flux: 3382-27,946Lm<sup>2</sup>
- Luminaire efficacy: 89Lm/W<sup>1</sup>
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90<sup>3</sup>
- Mac-Adams Ellipse: 3-SDCM
- LED type: Osram SMD LED
- Symmetrical distribution: 110°
- Outer trim Ø600-5000mm x Width 60mm x Height 68mm
- Mounting: Suspended; 3mtr adjustable
- Ingress protection rating: IP40
- Luminaire finishes: White, Black, Silver, Golden Bronze, Bronze, Champagne Gold; Custom optional<sup>4</sup>
- Longevity: >50,000Hrs L80 B20
- Driver: Non dimmable as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request<sup>4</sup>
- Weight: Ø600mm 6kg, Ø900mm 9kg, Ø1200mm 12kg, Ø1500mm 15kg, Ø2000mm 17kg, Ø2400mm 19kg, Ø3000mm 21kg, Ø4000mm 23kg, Ø5000mm 25kg (Exc. remote non-dimmable driver)
- Warranty: 5 years<sup>5</sup>

Model	Luminous Flux <sup>2</sup>	System Wattage	CCT	CRI <sup>3</sup>	Distribution
ZEN-60-D60-38W-3K	3,382Lm	38W	3000K	>90	110°
ZEN-60-D90-55W-3K	4,895Lm	55W	3000K	>90	110°
ZEN-60-D120-75W-3K	6,675Lm	75W	3000K	>90	110°
ZEN-60-D150-94W-3K	8,366Lm	94W	3000K	>90	110°
ZEN-60-D200-126W-3K	11,241Lm	126W	3000K	>90	110°
ZEN-60-D240-150W-3K	13,439Lm	150W	3000K	>90	110°
ZEN-60-D300-190W-3K	16,732Lm	190W	3000K	>90	110°
ZEN-60-D400-250W-3K	22,250Lm	250W	3000K	>90	110°
ZEN-60-D500-314W-3K	27,946Lm	314W	3000K	>90	110°

For Non-dimming add suffix ND

For DALI-2 dimming add suffix D

For BLUETOOTH dimming add suffix BT

Example product order code configuration: ZEN-60-D150-94W-3K-110-ND-(WH)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish
ZEN-60-D150	94W	3K	110	ND	WH

1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy

2 +/- 5% stated initial LED and luminous flux tolerance

3 Colour Rendering Index: >90 (Osram SMD Standard)

4 Additional charges apply for non-standard colour/s and dimming options


5 Five year manufacturer's warranty covering product defects and performance deficiencies

## Zen-60

### 38W-314W Suspended Circular Direct Illumination Luminaire

#### Light Distribution


ZEN-60-D150-94W-3K



AVERAGE BEAM ANGLE (50%): 104.9 DEG

Room Reflectance			Utilisation Factors											
			Room Index											
Ceiling	Walls	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00			
70	50	20	0.16	0.17	0.18	0.19	0.20	0.20	0.21	0.21	0.22			

#### Cone Diagram



- 1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
- 2 +/- 5% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >90 (Osram SMD Standard)
- 4 Additional charges apply for non-standard colour/s and dimming options
- 5 Five year manufacturer's warranty covering product defects and performance deficiencies