Project Type: Model:


Stitched-Up-PD45

12W / 15W Acoustic Rated Pendant



Luminaire Finishes

White (WH) Black (BK)



Accessories

Wire Suspension Kit (WSUS) Part No: SUSKIT-3M-SIL

Colour: Silver Length: 3m Adjustable

Wire Suspension Kit (WSUS) Part No: SUSKIT-3M-BLK Colour: Black

Length: 3m Adjustable

Length: 1m Adjustable

Length: 1m Adjustable

Rod Suspension Kit (RSUS) Part No: ROD-SUS-KIT-1M-WHT Colour: White

Rod Suspension Kit (RSUS)
Part No: ROD-SUS-KIT-1M-BLK
Colour: Black





Named after it's bold cross stitch pattern along the seam of this pendant, the Stitched-up is an acoustic pendant that can be tailored to suit a range of applications. Providing illumination of interior environments while reducing sound reverberation, it is useful in environments where noise is an issue such as hospitality, offices, residential, education and other commercial spaces.

Made from 5mm felt and a steel structure, the pendant comes in 4 sizes (450mm, 500mm, 600mm and 900mm diameters) and a range of colours, wattages and colour temperatures, allowing it to be fully customised to suit your project. The Stitched-up comes with a 5 year warranty.

- Luminaire wattage: 12W, 15W (System)
- Luminous flux: 1026-1142Lm, 1233-1383Lm²
- Luminaire efficacy: 84.82Lm/W, 85.69Lm/W¹
- Correlated colour temperature: 3000K, 4000K, 5000K (Dip-switch selectable)
- Colour rendering index: >853
- Mac-Adams Ellipse: 3-SDCM
- LED brand: OSRAM SMD LED
- Glare control: UGR<19
- Symmetrical distribution: 100°
- Dimension: Ø450 x Height 250mm
- Ingress protection rating: IP44 standard (LED Module)
- Luminaire finishes: White, Black
- Acoustic felt colours: 5mm (50 Colours)⁵
- Longevity: >50,000Hrs L80 B10
- Mounting: 3m adjustable wire suspensions
- Driver: Mains dimmable LED driver as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request⁴
- Weight: 2.25Kg (Inc. driver)
- Warranty: 5 years⁶

Model	Luminous Flux ²	LED Wattage	ССТ	CRI ³	Distribution	
STITCHED-UP-PD45-X-12W-3K	1026Lm	12W	3000K	>85	100°	
STITCHED-UP-PD45-X-12W-4K	1142Lm	12W	4000K	>85	100°	
STITCHED-UP-PD45-X-12W-5K	1092Lm	12W	5000K	>85	100°	
STITCHED-UP-PD45-X-15W-3K	1233Lm	15W	3000K	>85	100°	
STITCHED-UP-PD45-X-15W-4K	1383Lm	15W	4000K	>85	100°	
STITCHED-UP-PD45-X-15W-5K	1321Lm	15W	5000K	>85	100°	

For Mains-Dimming add suffix MD For DALI-2 dimming add suffix D For BLUETOOTH dimming add suffix BT


Replace X with WSUS for wire suspension Replace X with RSUS for rod suspension

Example product order code configuration: STITCHED-UP-PD45-WSUS-15W-TRI-100-MD-(WH/17/203)

Model	Suspension		1	Wattage		CCT Distrib		Distribution	on Driver			Luminaire Finish / PET Colour / Thread Colour			
STICHED-UP-PD45	+	WSUS	+	15W	+	TRI	+	100	+	MD	+	WH / 17 / 203			

Light Distribution


STITCHED-UP-PD45-15W-3K-100



AVERAGE BEAM ANGLE (50%): 97.3 DEG

Utilisation Factors												
Room	Reflect	tance	Room Index									
Ceiling	Walls	Floor		0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
70	50	20	-	89	93	98	101	104	105	107	110	111

Cone Diagram



- 1 Luminaire efficacy based on CCT 3000K; CCT variations will alter efficacy
- +/- 10% stated initial LED and luminous flux tolerance
- 3 Colour Rendering Index: >85 standard (OSRAM LED series)
- Additional charges apply for non-standard colour/s and dimming options
 Some colours may not be available at time of ordering. Please confirm with CoLab prior to ordering
- 6 Five year manufacturer's warranty covering product defects and performance deficiencies



Project Type: Model:

Stitched-Up-PD45

12W / 15W **Acoustic Rated Pendant**

Acoustic Felt 5mm⁵







Iconic



Pebble Bay



Cream Curd



Wizard Grey



Foxdale 06



Mobster 07



Black Sea 08



Black Fox 09



Black Earth



Star Anise



Passion Plum



Oriental Night



Oriska Sky



Blueberry Popover



Formosa Blue



Magical Merlin



Flax Flower



French Riviera



Mermaid Tail 20



Samba Dance



Lvy League



Killarney



Garden Medley



Oak Moss



Clover Hilltop



Jive Talk



Electric Neon 28



Gone Bananas 29



Lemon Spread 30



Orange Blaze



Orange Poppy



Hot Lips 33



Renegade 34



Rum Runner 35



Fuchsia Flock 36



Ruby Slippers



Blackberry Jam



Stormy Purple



Palisade Orchid



Muted Fuchsia

Belgian Waffle



Pink Persuasion



Chicory

46



English Saddle



Applesauce



Barefoot Beach

¹ Luminaire efficacy based on CCT 3000K; CCT variations will alter efficacy

^{+/- 10%} stated initial LED and luminous flux tolerance

Colour Rendering Index: >85 standard (OSRAM LED series)

Additional charges apply for non-standard colour/s and dimming options $Some\ colours\ may\ not\ be\ available\ at\ time\ of\ ordering.\ Please\ confirm\ with\ CoLab\ prior\ to\ ordering$

⁶ Five year manufacturer's warranty covering product defects and performance deficiencies




Project Type: Model:

Stitched-Up-PD45


12W / 15W **Acoustic Rated Pendant**





^{2 +/- 10%} stated initial LED and luminous flux tolerance

⁵ Some colours may not be available at time of ordering. Please confirm with CoLab prior to ordering





³ Colour Rendering Index: >85 standard (OSRAM LED series)

Additional charges apply for non-standard colour/s and dimming options