

Morq-A73

6W Adjustable Semi Recessed Downlight




Luminaire Finishes

White (WH) Black (BK)

Baffle Finish

Black (BK)



Ceiling cut-out Ø73mm / 6-25mm ceiling thickness

WATTAGE 6W
350° 50°
UGR <19
Bluetooth
Z
CE
WARRANTY 5YR

3-Step
CRI (Ra) >90
Ø 73
IP 20
20° / 38°

Morq-A73 is an LED semi-recessed architectural luminaire providing symmetrical, low-glare illumination. Quality manufactured and Italian designed, the semi-recessed downlight offers optimised and efficient performance. In either a classic white or solid black exterior with black baffle it suits a variety of residential and architectural applications.

Quality die-cast constructed with optical grade internal reflector for precise illumination, the Morq uses Zhaga compliant Citizen LED technology with a control gear from industry leading Tridonic. The fitting provides various dimming options including DALI-2 and Bluetooth wireless dimming and comes with a 5 year warranty.

- Luminaire wattage: 6W (System 8W)
- Luminous flux: 472-507Lm²
- Luminaire efficacy: 63.37Lm/W¹
- Correlated colour temperature: 2700K, 3000K
- Colour rendering index: >90³
- Mac-Adams Ellipse: 3-SDCM
- LED brand: Citizen SMD LED
- Glare control: <19
- Symmetrical distribution: 20°, 38°
- Outer trim: Ø80mm; Ceiling cut-out Ø73mm
- Ingress protection rating: IP20
- Luminaire finishes: White, Black
- Baffle options: Black
- Longevity: >50,000Hrs L80 B10
- Driver: Tridonic non-dimmable LED driver as standard
- Dimming: DALI-2, BLE (basicDIM Wireless /Casambi) on request⁴
- Weight: 290g (inc. non-dimmable driver)
- Warranty: 5 years⁵

Model	LED Output ²	Luminous Flux ²	LED Wattage	System Wattage	CCT	CRI ³	Distribution
MORQ-A73-6W-27K	688Lm	472Lm	6W	8W	2700K	>90	20°, 38°
MORQ-A73-6W-3K	740Lm	507Lm	6W	8W	3000K	>90	20°, 38°


For Non-dimming add suffix ND
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: MORQ-A73-6W-3K-20-ND-(WH/BK)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish / Baffle Finish					
MORQ-A73	+	6W	+	3K	+	20	+	D	+	WH/BK


Light Distribution

MORQ-A73-6W-3K-38



Utilisation Factors	
Room Reflectance	Room Index
Ceiling Walls Floor	1.00 2.00 3.00 4.00 5.00 6.00 7.00 8.00 9.00
70 50 20	1.08 1.01 0.94 0.88 0.83 0.78 0.74 0.70 0.66

Cone Diagram



1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
2 +/- 10% stated initial LED and luminous flux tolerance
3 Colour Rendering Index; >90 Standard (Citizen COB series)
4 Charges apply for non-standard colour/s and dimming options
5 Five year manufacturer's warranty covering product defects and performance deficiencies