


Kuppel-F100S

9W / 13W Fixed LED Recessed Downlight




Luminaire Finishes

White (WH) Black (BK)

Interchangeable Baffle Finishes

White (WH) Black (BK) Matt (MT)



WATTAGE 9W / 13W
IP 54
UGR <19
Bluetooth
Z
bati
CE
WARRANTY 5YR

3-Step
CRI (Ra) >90
100x100
60°

Recessed LED architectural luminaire series providing optimised and efficient performance with an IP54 rating and deep-set lamp source for symmetrical low glare distribution. Available in a range of wattage/lumen packages, the Kuppel series also offers various dimming options with screw adjustable wing mounting for easy installation.

Made from a die-cast aluminium housing with an aluminium reflector, it is available in a variety of finishes. Integrating Zhaga compliant Citizen LED technology and coupled with Tridonic control gear, the Kuppel series offers a 5 year warranty.

- Luminaire wattage: 9W, 13W (System 11W, 15W)
- Luminous flux: 900-950Lm, 1200-1300Lm²
- Luminaire efficacy: 122.22Lm/W, 115.38Lm/W¹
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90³
- Mac-Adams Ellipse: 3-SDCM
- LED Brand: Citizen COB LED
- Glare control: UGR<19
- Symmetrical distribution: 60°
- Outer Trim Width 110mm x Length 110mm; Ceiling cut-out Width 100mm x Length 100mm
- Ingress protection rating: IP54 standard (From underside)
- Luminaire finishes: White, Black
- Baffle Options: White, Black, Matt⁴
- Longevity: >50,000Hrs L80 B10
- Driver: Tridonic non-dimmable LED driver as standard
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request⁴
- Weight: 460g (excluding driver)
- Warranty: 5 years⁵

Model	LED Output ²	Luminous Flux ²	LED Wattage	System Wattage	CCT	CRI ³	Distribution
KUPPEL-F100S-9W-3K-60	1300Lm	900Lm	9W	11W	3000K	>90	60°
KUPPEL-F100S-9W-4K-60	1400Lm	950Lm	9W	11W	4000K	>90	60°
KUPPEL-F100S-13W-3K-60	1600Lm	1200Lm	13W	15W	3000K	>90	60°
KUPPEL-F100S-13W-4K-60	1700Lm	1300Lm	13W	15W	4000K	>90	60°


For Non-dimming add suffix ND
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: KUPPEL-F100S-13W-3K-60-D-(WH/WH)


Model	Wattage	CCT	Distribution	Driver	Luminaire Finish / Baffle Finish
KUPPEL-F100S	13W	3K	60	D	WH/WH

Light Distribution

KUPPEL-F100S-13W-3K-60



Cone Diagram



1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
2 +/- 10% stated initial LED and luminous flux tolerance
3 Colour Rendering Index: >90 Standard (Citizen COB series)
4 Charges apply for non-standard colour/s and dimming options
5 Five year manufacturer's warranty covering product defects and performance deficiencies