


## Zeroflex

### 10W / 15W COB Flexible LED Strip Lighting



#### Example profile options

**GHOST-1613-SM**  
W 16mm x H 13mm x L Custom



**GHOST-2013-SM**  
W 20mm x H 13mm x L Custom



**GHOST-2020-SM**  
W 20mm x H 20mm x L Custom



**GHOST-2525-SM**  
W 25mm x H 25mm x L Custom



**GHOST-3030-SM**  
W 30mm x H 30mm x L Custom



Zeroflex is an efficient and versatile 24V flexible LED system that provides a continuous line of light in LED strip lighting applications, eliminating the dotting effect often associated with low wattage or specific LED strip products. Available in different wattages and colour temperatures, Zeroflex has a multitude of options. The LED strip features advanced LED technology, high colour rendering capability as standard with 3-Step-MacAdam's single binning for high colour consistency.

The Zeroflex series has a range of direct and indirect applications whether it's to illuminate interior spaces or highlight architectural features. The product has optional DALI-2 or Bluetooth Wireless dimming upon request and comes with a 5 year warranty.

- Luminaire wattage/m: 10W, 15W
- Luminous flux/m: 900-1500Lm/m<sup>2</sup>
- Luminaire efficacy: 100Lm/W<sup>1</sup>
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90<sup>3</sup>
- Single Bin CCT selection
- LED Source / Quantity: COB Technology; 480pcs/m
- Symmetrical distribution: 180°
- Minimum cuttable section: 50mm
- Ingress protection rating: IP20
- Longevity: >50,000Hrs L80 B10
- Driver: Requires 24VDC constant voltage LED driver<sup>4</sup>
- Dimming: Remote DALI-2, BLE (basicDIM Wireless / Casambi) on request<sup>4</sup>
- Warranty: 5 years<sup>5</sup>

Model	Luminous Flux/m <sup>2</sup>	LED Wattage/m	CCT	CRI <sup>3</sup>	Distribution	Number of LED/m	Max. Continuous Length/m
ZEROFLEX-10W-3K	900Lm	10W	3000K	>90	180°	480	5m
ZEROFLEX-10W-4K	1000Lm	10W	4000K	>90	180°	480	5m
ZEROFLEX-15W-3K	1350Lm	15W	3000K	>90	180°	480	5m
ZEROFLEX-15W-4K	1500Lm	15W	4000K	>90	180°	480	5m


For Non-dimming add suffix ND  
For DALI-2 dimming add suffix D  
For BLUETOOTH dimming add suffix BT

Example product order code configuration: ZEROFLEX-10W-3K-ND

Model	Wattage	CCT	Driver
ZEROFLEX	10W	3K	ND

#### Light Distribution


ZEROFLEX-15W-3K



AVERAGE BEAM ANGLE (50%): 145.6 DEG

Room Reflectance	Utilisation Factors								
	Room Index								
Ceiling	0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
Walls	70	50	120	46	54	61	66	74	79
Floor	20	46	54	61	66	74	79	84	90

#### Cone Diagram



1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy  
2 +/- 10° stated initial LED and Luminous Flux tolerance  
3 Colour Rendering Index: >90 Standard  
4 Additional charges apply for non-standard colour/s and dimming options  
5 Five year manufacturer's warranty covering product defects and performance deficiencies