


## Tacca-F20

### 1W Fixed LED Recessed Downlight




Luminaire Finish

White (WH)

Glass Finish

Frosted (FR)



WATTAGE 1W
CRI (Ra) >90
IP 44
50°
Bluetooth
CE
WARRANTY 5YR

3-Step
Ø20
VOLTAGE 24V / 48V
MAINS DIM

LED ceiling recessed decorative luminaire providing symmetrical distribution. Quality constructed with a tiny, frosted glass tube protruding below the ceiling, Tacca-F20 is a unique alternative to traditional star point lighting and is well suited to dimly lit environments such as theatre rooms, hotel lobbies and bars.

Available in a range of colour temperatures and dimming options, Tacca-F20 comes with a 24V / 48V working voltage installation, making installation fast and safe. Comes in various dimming options such as DALI-2 and Bluetooth and offers a 5 year warranty.

- Luminaire wattage: 1W
- Luminous flux: 39-45Lm<sup>2</sup>
- Luminaire efficacy: 39Lm/W<sup>1</sup>
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90<sup>3</sup>
- Mac-Adams Ellipse: 3-SDCM
- LED Brand: Osram SMD LED
- Symmetrical distribution: 50°
- Outer trim Ø23mm; ceiling cut-out Ø20mm
- Ingress protection rating: IP44
- Luminaire finishes: White
- Glass colour: Frosted
- Longevity: >50,000Hrs L80 B10
- Driver: DC-DC driver; requires 24V remote driver<sup>4</sup>
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request, requires 48VDC remote driver<sup>4</sup>
- Weight: 25g (excluding driver)
- Warranty: 5 years<sup>5</sup>


Model	LED Output <sup>2</sup>	Luminous Flux <sup>2</sup>	LED Wattage	CCT	CRI <sup>3</sup>	Distribution
TACCA-F20-1W-3K-50	247Lm	39Lm	1W	3000K	>90	50°
TACCA-F20-1W-4K-50	260Lm	45Lm	1W	4000K	>90	50°

For Non dimming add suffix ND  
For MAINS dimming add suffix MD  
For DALI-2 dimming add suffix D  
For BLUETOOTH dimming add suffix BT


Example product order code configuration: TACCA-F20-1W-3K-50-ND-(WH/FR)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish / Glass Finish					
TACCA-F20	+	1W	+	3K	+	50	+	ND	+	WH/FR

#### Light Distribution



#### Cone Diagram



1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy  
2 +/- 10% stated initial LED and luminous flux tolerance  
3 Colour rendering index: >90 standard (OSRAM SMD Series)  
4 Requires 24V/48V LED Driver, not included. To be ordered separately  
5 Five year manufacturer's warranty covering product defects and performance deficiencies