

## Chopstix-0812-SM

### Surface Mounted Linear LED Profile



#### Luminaire Finishes

- White (WH)   
  Black (BK)   
  Custom  
 Natural Anodised (NA)

#### Profile

##### Aluminium Profile

Part No: Chopstix-0812-SM-AP  
Per metre

*For Black / White / Natural Anodised, add suffix -BK / -WH / -NA*



#### Accessories

##### Fixed Mounting Clips<sup>4</sup>

Part No: CHOPSTIX-0812-SM-MC  
Set of 2 pcs/set



##### End Caps

Part No: CHOPSTIX-0812-SM-EC  
Set of 2 pcs/set

*For Black / White / Silver, add suffix -BK / -WH / -SV*



Surface 

Recessed 

110° 

IP 44 

WARRANTY 5YR 

Chopstix linear profile series offers new lighting possibilities for a multitude of project applications due to its small size. Able to be surface or recessed mounted, it is perfect for handrails, joinery integration, task lighting and architectural features.


Constructed from high grade 6063T extruded aluminium with natural anodised surface treatment as standard, it provides optimal heat transfer and continuous illumination. Optional surface finishes are available to complement interior and/or exterior colour palettes. High quality opal PMMA diffusers enable harmonious distribution minimising the visibility of dots when used in conjunction with the Deltaflex-mini & Zeroflex-mini LED flex series.

- Mounting: Surface & recessed mounting applications
- Construction: Extruded 6063T grade aluminium mounting profile
- Finish Options: Natural anodised, White, Black and custom colours optional<sup>1</sup>
- Diffuser: Opal PMMA
- Symmetrical Distribution: 110°
- Accessories: Mounting clips & end caps included<sup>4</sup>
- Dimensions: W 8mm x H 12mm x L 2500mm
- Ingress protection rating: IP44
- Specifically designed for Zeroflex-mini and Deltaflex-mini LED series strip lights<sup>3</sup>
- Warranty: 5 years<sup>5</sup>


#### Compatible LED strip lighting<sup>2</sup>:

##### Deltaflex Mini<sup>3</sup>


12W – 120 LEDs/m

 2700K - 843Lm/m


 3000K - 876Lm/m

 4000K - 928Lm/m

10W – 120 LEDs/m


 294Lm/m


15W – 280 LEDs/m


 2700K - 6000K - 1318Lm/m

##### Zeroflex Mini<sup>3</sup>

8W - 480 LEDs/m

 2700K - 700Lm/m

 3000K - 763.45Lm/m

 4000K - 753.74Lm/m

7.8mm



<sup>1</sup> Natural Anodised standard; White, Matt Black or Custom colours will incur a surcharge

<sup>2</sup> LED strip not included

<sup>3</sup> Refer to Deltaflex-mini & Zeroflex-mini datasheet for detailed technical information

<sup>4</sup> Mounting clips are included on a basis of 2 pcs/m. Additional will incur a charge

<sup>5</sup> Five year manufacturer's warranty covering product defects and performance deficiencies