



Peeper-F33

3W Fixed LED Recessed Downlight



Luminaire Finishes

White (WH) Black (BK)



Ceiling cut-out Ø33mm / 6-25mm ceiling thickness

WATTAGE 3W
Ø33
UGR <19
Bluetooth
3-Step
CRI (Ra) >90
38°
IP 44
VOLTAGE 24V / 48V
WARRANTY 5YR

Peeper-F33 is a Decorative, LED, ceiling recessed luminaire providing symmetrical light distribution in a quality constructed fitting.

A miniature cutout, with a white frame and frosted glass lens allows Peeper to seamlessly blend in with its surrounds. Common applications include bathrooms, cut-out niches, bars and other environments where concealment of the light source or discrete architectural lighting is required.

Available in a range of colour temperatures and dimming options including DALI-2 and Bluetooth. With a 24V / 48VDC working voltage, installation is fast and safe. Peeper-F series comes with a 5 year warranty.

- Luminaire wattage: 3W
- Luminous flux: 221-232Lm²
- Luminaire efficacy: 73.66Lm/W¹
- Correlated colour temperature: 3000K, 4000K
- Colour rendering index: >90³
- Mac-Adams Ellipse: 3-SDCM
- LED Brand: Osram SMD LED
- Symmetrical distribution: 38°
- Outer trim Ø38mm; ceiling cut-out Ø33mm
- Ingress protection rating: IP44
- Luminaire finishes: White, Black
- Longevity: >50,000Hrs L80 B10
- Driver: DC-DC driver; requires 24VDC remote driver⁴
- Dimming: DALI-2, BLE (basicDIM Wireless / Casambi) on request; requires 48VDC remote driver⁴
- Weight: 50g (excluding driver)
- Warranty: 5 years⁵

Model	LED Output ²	Luminous Flux ²	LED Wattage	CCT	CRI ³	Distribution
PEEPER-F33-3W-3K	247Lm	221Lm	3W	3000K	>90	38°
PEEPER-F33-3W-4K	260Lm	232Lm	3W	4000K	>90	38°


For Non dimming add suffix ND
For DALI-2 dimming add suffix D
For BLUETOOTH dimming add suffix BT

Example product order code configuration: PEEPER-F33-3W-3K-38-ND-(WH)

Model	Wattage	CCT	Distribution	Driver	Luminaire Finish
PEEPER-F33	3W	3K	38	ND	WH


Light Distribution

PEEPER-F33-3W-3K-38



AVERAGE BEAM ANGLE (50%): 37.3 DEG

Cone Diagram



1 Luminaire efficacy based on CCT 3000K; CCT variation will alter efficacy
2 +/- 10% stated initial LED and luminous flux tolerance
3 Colour rendering index: >90 standard, (OSRAM SMD Series)
4 Requires remote 24V / 48VDC Constant voltage non-dimmable driver. To be ordered separately
5 Five year manufacturer's warranty covering product defects and performance deficiencies