

Graze-2109-REC

Recessed  110°  IP 44  WARRANTY 5YR

Recessed Mounted Linear LED Profile



Luminaire Finishes

- White (WH)
 Black (BK)
 Custom
 Natural Anodised (NA)

Profile

Aluminium Profile

Part No: GRAZE-2109-REC-AP
Per metre

For Black / White / Natural Anodised, add suffix -BK / -WH / -NA



Graze linear profile series offers new lighting possibilities for a range of project applications. Pitched LED mounting enables grazing and other angled lighting distribution effects. Perfect for joinery integration, task lighting and architectural features.

Constructed from high grade 6063T extruded aluminium with natural anodised surface treatment as standard, allowing optimal heat transfer and continuous illumination. Uses a high quality opal PMMA diffuser with optional surface finishes available. Perfectly suited to the Deltaflex-mini and Zeroflex-mini series of LED strip lighting.

- Mounting: Recessed mounting applications
- Construction: Extruded 6063T grade aluminium mounting profile
- Finish Options: Natural anodised, White, Black and custom colours optional¹
- Diffuser: Opal PMMA
- Symmetrical Distribution: 110°
- Dimensions: W 21mm x H 9mm x L 2500mm
- Ingress protection rating: IP44
- Specifically designed for Zeroflex-mini and Deltaflex-mini LED series strip lights³
- Warranty: 5 years⁴


Compatible LED strip lighting²:

Deltaflex-mini³

12W - 120 LEDs/m

 2700K - 843Lm/m


 3000K - 876Lm/m

 4000K - 928Lm/m

15W - 280 LEDs/m


 2700-6000K - 1318Lm/m


10W - 120 LEDs/m


 294Lm/m

Zeroflex-mini³

8W - 480 LEDs/m

 2700K - 700Lm/m

 3000K - 763.4Lm/m

 4000K - 753.7Lm/m

