co:lab

Project Type:

CO.IUD			Type: Model:
Blackout-5035-REC	Recessed 110°	IP 44 💧 WARRANTY 5YR	I
Recessed Mounted Linear LED Profile			
	The Blackout linear profile se profile that combines a black high quality black anodised of applications, when used in the profile seamlessly blends until illuminated. Constructed from high grade and high quality translucent provides optimal heat transf illumination. The profile can Zeroflex ³ range of flexible LEI dotting effect. The Blackout i recessed applications.	k coloured diffuser with a profile. Suitable for a range n areas with black surfaces s in with it's environment e 6063T extruded aluminium black PMMA, the Blackout er and continuous also be paired with the D strip lighting for that NO	 Mounting: Recessed mounting applications Construction: Extruded 6063T grade aluminium mounting profile Finish Options: Black¹ Diffuser: PMMA Translucent black Symmetrical Distribution: 110° Accessories: Mounting clips & end caps included⁴ Dimensions: W 50mm x H 35mm x Custom Length Ingress protection rating: IP44 Specifically designed for Zeroflex series LED strip lighting³ Warranty: 5 years⁵
Luminaire Finish	Compatible LED strip lighting	² :	
Black (BK)	Zeroflex ³		
Profile	10W - 480 LEDs/m 	3000K - 900Lm/m 3000K - 1350Lm/m	4000K - 1000Lm/m
Aluminium Profile Part No: Blackout-5035-REC-AP Per metre	50mm		4000 1000211711
Accessories Recessed Mounting Clips Part No: BLACKOUT-5035-REC-MC Set of 2 pcs/set	۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲ ۲	Simmer	19 19 19 19 19 19 19 19 19 19 19 19 19 1
End Caps Part No: BLACKOUT-5035-REC-EC Set of 2 pcs/set			



1 Black finish as standard

- 2 LED strip not included

Refer to Zeroflex datasheet for detailed technical information
 Mounting clips are included on a basis of 2 pcs/m. Additional will incur a charge
 Five year manufacturer's warranty covering product defects and performance deficiencies